

Tactical 4-16x42AO IR Riflescope

SPECIFICATIONS

| MIL-DOT | Maximum recoil (G's) | 1200G |
|-------------|---|--|
| red green | Battery type | CR2032 |
| Yes | Battery life (hours) | 80-150 |
| 1-5 | Waterproof/nitrogen filled | Yes |
| 4-16 | Shock and Fog proof | Yes |
| 42 | Operating temperature (°C) | -20°- 60°C |
| 8.73 - 2.33 | Dimensions (mm) | 340x80x56 |
| 26.2 - 6.98 | Weight (oz) | 26.5 |
| +2 -2 | FEATURES • Internal lit red/green reticle | |
| 25.4mm | | |
| 53mm | | |
| 41mm | Adjustable objective lens Second focal plane system Locking turrets Waterproof / fog proof | |
| 1/4MOA | | |
| 15∞ yds | | |
| | red green Yes 1-5 4-16 42 8.73 - 2.33 26.2 - 6.98 +2 -2 25.4mm 53mm 41mm | red greenBattery typeYesBattery life (hours)1-5Waterproof/nitrogen filled4-16Shock and Fog proof42Operating temperature (°C)8.73 - 2.33Dimensions (mm)26.2 - 6.98Weight (oz)+2 -2FEATURES53mm· Internal lit red/green reticle · Adjustable objective lens · Second focal plane system · Locking turrets · Waterproof / fog proof |

Yes

INCLUDED ACCESSORIES

• Flip up lens covers

• 1 inch Riflescope Rings

Windage & Elevation lock